

### Model Number Example

Features: SPDT, 50Ω Terminations, SMA, Latching, Indicators, Self Cutoff, 26.5GHz, 12VDC, TTL, Transient Diodes, 9 Pin D-Sub, Ruggedized

**1 2 T- S2L5 -2612-T J F - R**

X X X - XX XX- XX XX- X \_ \_ - X

Number of inputs (≥1)	1
Number of outputs (≥2)	2

Model Type	
Standard	S
Narrow Body (1)	N
Internal Termination (2)	T
External Termination (2)	E

Connector Type	
SMA	S2
SMB	S3
SC	S4
N	N2
TNC	T2
RF Pin	P2
BNC	B2
F (75 ohms)	F2
2.92mm	M2
7/16 DIN	D7
4.3-10 DIN	D4
Special	X2

Actuator Type	
Failsafe	F2
Failsafe, ind	F3
Failsafe, +com	F4
Failsafe, ind, +com	F5
Latching	L2
Latching, ind	L3
Latching, SC	L4
Latching, ind, SC	L5
Latching, +com	L6
Latching, +com, ind	L7
Latching, , +com, SC	L8
Latching, , +com, ind, SC	L9
Normally Open (3)	N2
Normally Open, ind (3)	N3
Normally Open, +com (3)	N4
Normally Open, +com, ind (3)	N5

Special	
L	Lo-PIM
R	Ruggedized
C	Custom Design

Options	
T	TTL Driver
D	TTL Decoder
J	Transient Suppression diodes
A	Auto Reset
	<i>Solder Pin/Lug (SPDT/TRAN) (4)</i>
F	9 Pin D-Sub connector (SPDT/TRAN)
	<i>15 Pin D-Sub connector (SPMT) (5)</i>
H	16 Pin D-Sub connector (SPMT)
P	Solder Pin/Lug (SPMT)
M	Mositure Seal (resistant/proof)
X	Special

Actuator Voltage	
05	5 VDC
12	12 VDC
15	15 VDC
18	18 VDC
20	20 VDC
24	24 VDC
28	28 VDC
48	48 VDC

Frequency Range	
03	DC-3 GHz
06	DC-6 GHz
08	DC-8 GHz
12	DC-12 GHz
18	DC-18 GHz
20	DC-20 GHz
22	DC-22 GHz
26	DC-26.5 GHz
33	DC-33 GHz
XX	Special

#### Notes:

- (1) SPDT models only
- (2) SPDT and SPMT models, excluding N2, T2, D7 and D4 connectors
- (3) SPMT models only
- (4) Solder pins are standard for SPDT and TRAN models, no designation on model number needed
- (5) D-Sub 15 pin connector is standard for SPMT models, no designation on model number needed

